

HMT130 Humidity and Temperature Transmitter

		1	2	3	4	5	6	7	8	9	10	11	12	13	14	Price
Vaisala HUMICAP® Humidity and Temperature Transmitter		HMT130														
Output parameters	Humidity output only															
	Humidity and temperature output															
Transmitter type	Wall mount/ fixed probe															
	Remote probe with 3 m cable															
	Remote probe with 5 m cable															
	Remote probe with 10 m cable															
	Remote probe with 10 m cable + 10 m extension															
	Remote probe with 20 m cable															
Display	No display															
	Display															
Analog output signal (RS485 also included)	0...1 V															
	0...5 V															
	0...10 V															
SPECIAL	Define scale: 3-wire _____ V *)															
Parameter for Output 1	RH															
	Tdf															
	H															
	Tw															
	a															
	x															
	Pw															
	Pws															
	Td															
	SPECIAL	Define quantity _____ Scale _____														
Parameter for Output 2	None															
	T															
SPECIAL	Define quantity _____ Scale _____															
Display Units	Metric															
	Non metric															
Sensor protection	Plastic grid															
	Plastic grid with PTFE filter															
	Stainless steel sintered filter (for remote probes only)															
Transmitter installation	No accessories															
	Rainshield with installation kit (215109)															
Installation kit for probe	No accessories															
	Duct installation kit (215619)															
	Probe mounting flange (226061)															
	Outdoor installation: DTR504A Radiation Shield with probe installation kit (DTR504A)															
	Probe mounting clamp, 1 piece (225501)															
Cable bushings	Cable gland for 2...6 mm diameter cable															
	Conduit fitting PG9															
	Conduit fitting NPT 1/2"															
	No bushing (rubber plug)															
	All bushings (includes A, B, C and D)															
PC Accessories	No															
	Service cable for PC, USB (219685)															
Operation manual	No manual															
	Multilingual															
															Total	
															QTY	
															Total value	

*) Voltage output value between 0...10 V

Selections in bold are included in the prices of the basic versions
Selections in *italic* are available at an extra cost

Example of order code with typical settings

HMT130	K	A	1	D	1	B	0	1	1	A	1	A	0	Z
--------	---	---	---	---	---	---	---	---	---	---	---	---	---	---

HMT130 Temperature Transmitter

		1	2	3	4	5	6	7	8	9	10	11	12	13	14	Price
Vaisala HUMICAP® Temperature Transmitter		HMT130	T					A	0							
Output parameters		Temperature output only														
Transmitter type		Wall mount/fixed probe														
		<i>Remote probe with 3 m cable</i>														
		<i>Remote probe with 5 m cable</i>														
		<i>Remote probe with 10 m cable</i>														
		<i>Remote probe with 10 m cable + 10 m extension</i>														
		<i>Remote probe with 20 m cable</i>														
Display		No display														
		<i>Display</i>														
Analog output signal (RS485 also included)		0...1 V														
		3-wire														
		0...5 V														
		3-wire														
		0...10 V														
		3-wire														
SPECIAL		Define scale: 3-wire _____ V *)														
Parameter for Output 1		T														
		-40...+60 °C (-40...+140 °F)														
		-20...+80 °C (-4...+176 °F)														
		0...+60 °C (+32...+140 °F)														
		-40...+80 °C (-40...+176 °F)														
		0...+50 °C (+32...+122 °F)														
SPECIAL		Define quantity _____ Scale _____														
Parameter for Output 2		None														
Display Units		Metric														
		Non metric														
Sensor protection		Plastic grid														
		Plastic grid with PTFE filter														
		Stainless steel sintered filter (for remote probes only)														
Transmitter installation		No accessories														
		<i>Rain shield with installation kit (215109)</i>														
Installation kit for probe		No accessories														
		<i>Duct installation kit (215619)</i>														
		<i>Probe mounting flange (226061)</i>														
		<i>Outdoor installation: DTR504A Radiation Shield with probe installation kit (DTR504A)</i>														
		<i>Probe mounting clamp, 1 piece (225501)</i>														
Cable bushings		Cable gland for 2...6 mm diameter cable														
		Conduit fitting PG9														
		Conduit fitting NPT 1/2"														
		No bushing (rubber plug)														
		<i>All bushings (includes A, B, C and D)</i>														
PC Accessories		No														
		<i>Service cable for PC, USB (219685)</i>														
Operation manual		No manual														
		Multilingual														
Total																
QTY																
Total value																

*) Voltage output value between 0...10 V

Selections in bold are included in the prices of the basic versions
Selections in italic are available at an extra cost

Example of order code with typical settings

HMT130	T	A	1	D	B	A	0	1	A	1	1	A	0	Z
--------	---	---	---	---	---	---	---	---	---	---	---	---	---	---